



Specifications Philips LED Downlight  
Coreline DN142B Aluminium White  
10.7W 1200lm 60D - 840 Cool White |  
Cutout 155mm - IP54 - UGR<19 -  
Dimmable

[View Product](#)

## General Information

|                          |                                 |
|--------------------------|---------------------------------|
| SKU                      | 248710                          |
| EAN                      | 8720169108943                   |
| Brand                    | Philips                         |
| Manufacturer Name        | DN142B 10S/840 PSD-E UGR19 IP54 |
| Any Lamp all-in warranty | 5 Years                         |
| Average Lifetime (h)     | 50000                           |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Dimmable          |
| Colour Code                 | 840 Cool White    |
| Colour temperature (Kelvin) | 4000 Cool White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |
| Beam Angle (degree)         | 60                |
| Luminous Efficacy (lm/W)    | 112               |

|                       |                                |
|-----------------------|--------------------------------|
| Power factor          | >0.95                          |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PC (Polycarbonate)             |
| Product Type Category | LED Downlight                  |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| EOC8                   | 10894300                      |
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 155                           |
| IP-rating              | IP54                          |
| Impact Protection (IK) | IK03 - 0.35 joule             |
| Operating Temperature  | -20 to +40                    |
| Housing                | Aluminium                     |
| Colour of the Fixture  | White                         |
| Fixture Connection     | PI [Push-in connector 6-pole] |
| Series                 | DN142B                        |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 82  |
| Diameter (mm) | 162 |

## Sensor Information

|                |                                   |
|----------------|-----------------------------------|
| Type of sensor | <b>Why Any-lamp?</b><br>No Sensor |
|----------------|-----------------------------------|



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

